

REM-9

(E-4)
HAULAGE



FEATURES & BENEFITS

- Unique non-directional tread design for added traction
- Special compounds to withstand severe rock mining applications and extend tire life/promote retreadability
- Compounds: **A** cut/chip; **S** standard; **B** heat

PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX/LOAD PRESSURE (LBS/PSI)	TIRE WEIGHT	NOTE
1087206252	26.5R25	REM-9A	★★	50	30	70	27	69	22.00/3.0	25300lbs/76psi	540kg/1155lbs	E4
1087206253	26.5R25	REM-9S	★★	50	30	70	27	69	22.00/3.0	25300lbs/76psi	540kg/1155lbs	E4
1087206254	26.5R25	REM-9B	★★	50	30	70	27	69	22.00/3.0	25300lbs/76psi	540kg/1155lbs	E4
1087202955	29.5R25	REM-9A	★★	50	30	75	30	76	25.00/3.5	30800lbs/76psi	650kg/1397lbs	E4
1087202956	29.5R25	REM-9S	★★	50	30	75	30	76	25.00/3.5	30800lbs/76psi	650kg/1397lbs	E4
1087202957	29.5R25	REM-9B	★★	50	30	75	30	76	25.00/3.5	30800lbs/76psi	650kg/1397lbs	E4
1087201833	18.00R33	REM-9A	★★	50	30	73	20	69	13.00/2.5	23980lbs/102psi	470kg/1012lbs	E4
1087201834	18.00R33	REM-9S	★★	50	30	73	20	69	13.00/2.5	23980lbs/102psi	470kg/1012lbs	E4
1087201835	18.00R33	REM-9B	★★	50	30	73	20	69	13.00/2.5	23980lbs/102psi	470kg/1012lbs	E4
1087202452	24.00R35	REM-9A	★★	50	30	85	26	87	17.00/3.5	40700lbs/102psi	777kg/1698lbs	E4
1087202453	24.00R35	REM-9S	★★	50	30	85	26	87	17.00/3.5	40700lbs/102psi	777kg/1698lbs	E4
1087202454	24.00R35	REM-9B	★★	50	30	85	26	87	17.00/3.5	40700lbs/102psi	777kg/1698lbs	E4
1087202798	27.00R49	REM-9A	★★	50	30	106	29	94	19.50/4.0	59950lbs/102psi	1412kg/3113lbs	E4
1087202796	27.00R49	REM-9S	★★	50	30	106	29	94	19.50/4.0	59950lbs/102psi	1412kg/3113lbs	E4
1087202797	27.00R49	REM-9B	★★	50	30	106	29	94	19.50/4.0	59950lbs/102psi	1412kg/3113lbs	E4
1087202135	21.00R33	REM-9B	★★	50	30	77.4	22.3	69	15.00/3.0	30864lbs/102psi	567kg/1250lbs	E4