

REM-2

 (E-3/L-3)
EARTHMOVER/LOADER


FEATURES & BENEFITS

- Enhanced self-cleaning design for all purpose applications
- Multi-function, non-directional tread design for optimum usage on equipment
- Superior traction in sand, stone, mud and other surfaces
- OEM Certified

PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX/LOAD PRESSURE (LBS/PSI)	TIRE WEIGHT	NOTE
1107147251	17.5R25	REM-2	★	50	30	53	18	34	14.00/1.5	9075lbs/54psi	153kg/331lbs	E3/L3
"	"	"	"	10	5	53	18	34	14.00/1.5	15620lbs/73psi	153kg/331lbs	E3/L3
1107140251	20.5R25	REM-2	★	50	30	58	21	39	17.00/2.0	12320lbs/54psi	229kg/488lbs	E3/L3
"	"	"	"	10	5	58	21	39	17.00/2.0	20900lbs/73psi	229kg/488lbs	E3/L3
1107143251	23.5R25	REM-2	★	50	30	64	24	45	19.50/2.5	15620lbs/54psi	336kg/719lbs	E3/L3
"	"	"	"	10	5	64	24	45	19.50/2.5	26730lbs/73psi	336kg/719lbs	E3/L3
1107146252	26.5R25	REM-2	★	50	30	69	27	47	22.00/3.0	19800lbs/54psi	461kg/1020lbs	E3/L3
"	"	"	"	10	5	69	27	47	22.00/3.0	33000lbs/73psi	461kg/1020lbs	E3/L3
1107167251	17.5R25	REM-2	★★	50	30	53	18	34	14.00/1.5	11990lbs/76psi	157kg/338lbs	E3/L3
"	"	"	"	10	5	53	18	34	14.00/1.5	18700lbs/94psi	157kg/338lbs	E3/L3
1107160251	20.5R25	REM-2	★★	50	30	58	21	39	17.00/2.0	16060lbs/76psi	231kg/491lbs	E3/L3
"	"	"	"	10	5	58	21	39	17.00/2.0	25300lbs/94psi	231kg/491lbs	E3/L3
1107163251	23.5R25	REM-2	★★	50	30	64	24	45	19.50/2.5	20350lbs/76psi	336kg/721lbs	E3/L3
"	"	"	"	10	5	64	24	45	19.50/2.5	31900lbs/94psi	336kg/721lbs	E3/L3
1107166252	26.5R25	REM-2	★★	50	30	69	27	47	22.00/3.0	25300lbs/76psi	463kg/1023lbs	E3/L3
"	"	"	"	10	5	69	27	47	22.00/3.0	40700lbs/94psi	463kg/1023lbs	E3/L3
1107162955	29.5R25	REM-2	★★	50	30	73	29	50	25.00/3.5	30800lbs/76psi	587kg/1274lbs	E3/L3
"	"	"	"	10	5	73	29	50	25.00/3.5	49280lbs/94psi	587kg/1274lbs	E3/L3