

# RLB200+

PREMIUM ON AND OFF HIGHWAY  
DRIVE POSITION TIRE



## FEATURES & BENEFITS

- Aggressive directional tread pattern for improved traction and handling
- Extra wide tread for enhanced tread life and handling

| PRODUCT CODE | TIRE SIZE   | PLY RATING | LOAD INDEX | SPEED SYMBOL | OVERALL DIAMETER (INCH) | SECTION WIDTH (INCH) | TREAD DEPTH (32NDS) | RIM  | SINGLE MAX/LOAD PRESSURE | DUAL MAX/LOAD PRESSURE | STATIC LOAD RADIUS | REVS PER MILE | WEIGHT |
|--------------|-------------|------------|------------|--------------|-------------------------|----------------------|---------------------|------|--------------------------|------------------------|--------------------|---------------|--------|
| 1133731256   | 11R22.5     | 16         | 148/145    | J            | 41.7                    | 11.1                 | 25                  | 8.25 | 6940lbs/123psi           | 6390lbs/123psi         | 19.8               | 493           | 124    |
| 1133732256   | 12R22.5     | 16         | 150/147    | J            | 43.1                    | 11.7                 | 26                  | 9.00 | 7390lbs/120psi           | 6780lbs/120psi         | 20.5               | 480           | 156    |
| 1133732258   | 12R22.5     | 18         | 152/149    | M            | 43.1                    | 11.7                 | 26                  | 9.00 | 7830lbs/135psi           | 7160lbs/135psi         | 20.5               | 480           | 156    |
| 1133731257   | 315/80R22.5 | 18         | 156/154    | L            | 42.8                    | 12.2                 | 26                  | 9.00 | 8820lbs/120psi           | 8270lbs/120psi         | 20.2               | 478           | 160    |
| 1133731258   | 315/80R22.5 | 20         | 157/154    | J            | 42.8                    | 12.2                 | 26                  | 9.00 | 9090lbs/130psi           | 8270lbs/120psi         | 20.2               | 478           | 160    |
| 1133732247   | 12.00R24    | 18         | 158/155    | J            | 48.4                    | 12.3                 | 24                  | 8.50 | 9370lbs/120psi           | 8540lbs/120psi         | 22.7               | 423           | 187    |
| 1133732248   | 12.00R24    | 20         | 160/157    | J            | 48.4                    | 12.3                 | 24                  | 8.50 | 9920lbs/130psi           | 9090lbs/130psi         | 22.7               | 423           | 187    |