

RR680

PREMIUM REGIONAL AND
ALL-POSITION STEER TIRE



FEATURES & BENEFITS

- Premium 5-rib tread design with wide shoulders provides for durability and even wear in steer and all-position applications
- Deep $19/32$ " original tread depth provides long original tread life
- Enhanced channel siping and wide grooves allow for premium wet and dry traction

PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX/LOAD PRESSURE	DUAL MAX/LOAD PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT
1133679214	9R22.5	14	136/134	L	38.3	9.1	18	6.75	4940lbs/120psi	4675lbs/120psi	17.9	206	110
1133671255	11R22.5	14	144/142	L	41.4	11.1	20	8.25	6175lbs/105psi	5840lbs/105psi	19.8	499	115
1133671256	11R22.5	16	148/145	L	41.4	11.1	20	8.25	6940lbs/123psi	6390lbs/123psi	19.8	499	118
1133679255	295/75R22.5	14	144/141	M	40.6	11.7	20	9.00	6175lbs/110psi	5675lbs/110psi	19.5	504	118
1133671455	11R24.5	14	146/143	L	43.3	10.9	20	8.25	6610lbs/105psi	6005lbs/105psi	20.8	476	129
1133671456	11R24.5	16	149/146	L	43.3	10.9	20	8.25	7160lbs/120psi	6610lbs/120psi	20.8	476	132
1133678455	285/75R24.5	14	144/141	L	41.5	11.0	20	8.25	6175lbs/110psi	5675lbs/110psi	19.5	492	124
1133679256	295/80R22.5	16	150/147	M	41.3	11.9	18	9.00	7390lbs/120psi	6780lbs/120psi	19.8	491	120
1133679258	295/80R22.5	18	152/149	M	41.3	11.9	18	9.00	7830lbs/130psi	7160lbs/130psi	19.8	491	120
1133671258	315/80R22.5	20	157/154	L	42.4	12.2	18	9.00	9090lbs/130psi	8270lbs/130psi	19.9	488	142
1133670456	305/75R24.5	16	154/149	M	42.7	11.6	19	9.00	8270lbs/123psi	7160lbs/123psi	N/A	N/A	145